

LT7911UX --- Product Brief

Type-C/DP to Quad-port MIPI with Audio

Features

● USB Type-C

- Compliant with VESA DisplayPort Alt Mode on USB Type-C standard V1.0
- Compliant with USB Power Delivery specification R3.0, V1.0
- Compliant with USB Type-C Cable and Connector specification R1.3
- Built-in dual CC controllers for charger and normal communication
- 3 data roles supported: DFP, UFP and DRP
- 2 power roles supported: source and sink

● DP1.4 Receiver

- Compliant with the DP1.4 specification with data rates up to 8.1Gbps per channel
- Support HDCP 1.3/2.2/2.3
- Support HDR
- Support FEC
- Support 8k@30Hz, 8k@60Hz with DSC

● Single/Dual/Quad-Port MIPI® DSI/CSI Transmitter

- Compliant with D-PHY1.2 & DSI 1.3 & CSI-2 1.3, C-PHY1.0 & DSI-2 1.0 & CSI-2 2.0
- 1/2/4 configurable port
- D-PHY: 1~4 Configurable Data Lanes per port
- C-PHY: 1~3 Configurable Data Lanes per port
- D-PHY: 2.5Gb/s per data lane
- C-PHY: 5.7Gb/s per data lane
- Data lane and polarity swapping
- Support video overlap
- Support RGB/YUV4:2:2/YUV4:4:4/YUV 4:2:0 8/10bit Video Format
- Side-by-side 3D support
- Support CSI D-option 8 Lane output

● Miscellaneous

- 3.3V/1.1V Supply Power
- VESA DSC v1.2a (v1.1 compatible)
- Zoom scaling up and down
- Support FRC
- Support Rotation(Max 1080P)
- CSC: RGB <-> YUV444 <-> YUV422<-> YUV420
- Support SPDIF and 8-channel IIS audio output
- Support 100KHz and 400KHz I2C slave
- Power from phone or adapter mode selection
- Integrated Microprocessor
- Temperature Range: -40°C ~ +85°C
- ESD 4kV HBM
- Embedded LPDDR3/4 DRAM

Description

The LT7911UX is a high performance Type-C/DP1.4 to MIPI chip for VR/Display application.

HDCP RX as the upstream of HDCP repeater, can cooperate with HDCP TX of other chips to realize the repeater function.

For DP1.4 input, LT7911UX can be configured as 1/2/4 lane, also support lane swap function. Adaptive equalization makes it suitable for long cable application and the maximum bandwidth is up to 32.4Gbps.

For MIPI output, LT7911UX features configurable single-port or dual-port or quad-port MIPI®DSI/CSI with 1 high-speed clock lane and 1~4 high-speed data lanes operating at maximum 2.5Gb/s/lane with D-PHY, which can support a total bandwidth of up to 40Gbps. Or support 5.7Gb/s/lane with C-PHY, which can support a total bandwidth of up to 68.4Gbps.

LT7911UX is fabricated in advanced CMOS process and implemented in 9mmx9mm BGA169 package. This package is RoHS compliant and specified to operate from -40°C to +85°C.

Applications

- Mobile system
- Display
- VR



Figure1. Application Diagram

Ordering Information

Part Number	Operating Temperature Range	Package	Packing Method
LT7911UX	-40°C to +85°C	BGA169 (9*9)	Tray

Copyright © 2019-2020 Lontium Semiconductor Corporation, All rights reserved.

Lontium Semiconductor Proprietary & Confidential

This document and the information it contains belong to Lontium Semiconductor. Any review, use, dissemination, distribution or copying of this document or its information outside the scope of a signed agreement with Lontium is strictly prohibited.

LONTIUM DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THOSE OF NONINFRINGEMENT, MERCHANTABILITY, TITLE AND FITNESS FOR A PARTICULAR PURPOSE. CUSTOMERS EXPRESSLY ASSUME THEIR OWN RISK IN RELYING ON THIS DOCUMENT.

LONTIUM PRODUCTS ARE NOT DESIGNED OR INTENDED FOR USE IN LIFE SUPPORT APPLIANCES, DEVICES OR SYSTEMS WHERE A MALFUNCTION OF A LONTIUM DEVICE COULD RESULT IN A PERSONAL INJURY OR LOSS OF LIFE.

Lontium assumes no responsibility for any errors in this document, and makes no commitment to update the information contained herein. Lontium reserves the right to change or discontinue this document and the products it describes at any time, without notice. Other than as set forth in a separate, signed, written agreement, Lontium grants the user of this document no right, title or interest in the document, the information it contains or the intellectual property it embodies.

Trademarks

Lontium™ 龙迅™ and ClearEdge™ is a registered trademark of Lontium Semiconductor. All other brand names, product names, trademarks, and registered trademarks contained herein are the property of their respective owners.

Visit our corporate web page at: www.lontiumsemi.com

Technical support: support@lontium.com

Sales: sales@lontium.com